

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representation of
The original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)

(19)



Eur päisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 909 920 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
21.04.1999 Bulletin 1999/16

(51) Int. Cl.⁶: **F23D 11/38**, F23D 11/26,
F02M 61/16, F02M 61/18

(21) Application number: 98116458.5

(22) Date of filing: 31.08.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 24.09.1997 US 936247

(71) Applicant:
Siemens Automotive Corporation
Auburn Hills, Michigan 48326-2980 (US)


(72) Inventors:
• **Shen, Jingming Jim**
Newport News, VA 23608 (US)

• **Ren, Wei-Min**
Yorktown, VA 23698 (US)
• **Wieczorek, David P.**
Seaford, VA 23696 (US)
• **Huszar, Gyula A.**
Newport News, VA 23602 (US)

(74) Representative:
Allen, Derek et al
Siemens Group Services Limited,
Intellectual Property Department,
Siemens House,
Oldbury
Bracknell, Berkshire RG12 8FZ (GB)

(54) Pressure swirl injector with angled cone spray for fuel injection

(57) A fuel injector has a swirl plate (48) about a valve assembly, including a valve seat (34) with an orifice (32) and a valve pin (20). When the valve is opened, the fuel is swirled by the swirl plate for passage through the orifice. The orifice has a portion which is angled relative to the axis of the injector to provide a conical swirling spray pattern (68) having a conical spray axis (66) angularly related to the axis (64) of the injector. In another form, the orifice is on-axis with the injector and receives a bent tube (72) having an upstream on-axis portion and a downstream angled portion to direct the swirling conical spray at an included obtuse angle relative to the axis of the injector.



EP 0 909 920 A1

Description

TECHNICAL FIELD

[0001] The present invention relates to injectors for injecting fuel into an internal combustion engine and particularly relates to a pressure swirl-type injector for ejecting fuel in a swirling conical spray pattern with an axis offset or angled relative to the axis of the fuel injector for flowing the swirling conical spray pattern in a desired direction.

BACKGROUND

[0002] Fuel injectors in general have long been used for injecting fuel into an internal combustion engine. Such fuel injectors typically include an elongated body having an armature carrying a valve and a needle or pin which, under the bias of a spring, normally closes an orifice through a seat at one end of the injector. By periodically pulsing a coil within the injector body, the valve is periodically opened and closed to supply fuel through the orifice to the engine cylinder. Typically, the spray pattern flowing from the injector is in a swirling conical shape. It is quantitatively dominated by an outer conical wall of spray, with substantially smaller quantities of the fuel from the injector flowing interiorly within the conically-shaped spray. The axis of the conical spray pattern is generally directed to an optimal part of the engine or fuel injection system and the injector is normally oriented so that the injector axis and the conical spray pattern axis are coincident with one another.

[0003] In certain engines, however, constraints imposed on the mounting of the injectors have indicated a need for directing the conical spray to the optimum part of the engine or fuel injection system, while simultaneously mounting the injector at a location and in a position wherein the axis of the injector does not coincide with the axis of the conical spray pattern. Consequently, a problem arises as to how to simultaneously direct a swirling conical spray pattern to the optimal part of the engine or fuel injection system while enabling the injector to be mounted at an angle offset from the axis of the conical spray pattern.

[0004] One effort to direct a conical spray pattern having a swirl associated with the pattern is disclosed in an article appearing in SAE Publication 970540, titled "Development of Direct Injection Gasoline Engine." The injector disclosed in that article, has what appears to be a spray pattern inclined at an angle from the axis of the injector, an upstream swirler and a downstream orifice apparently angled off the longitudinal axis of the injector. However, an intermediate chamber or pocket lies between the swirler and the angled orifice of that injector and which chamber is enlarged relative to the orifice. The pocket, however, diminishes the swirl pattern to such an extent that when the fuel leaves the injector such fuel is not significantly swirling. That is, the swirl

pattern effected by the swirler upstream of the valve seat is substantially diminished as the fuel leaves the valve seat and enters and exits the pocket. Because of the many angled surfaces defining the pocket, it detrimentally diminishes the effect of the swirl pattern imparted upstream of the pocket by the swirler to the extent that the conical spray emitted from the injector has very little, if any, swirl effect.

DISCLOSURE OF THE INVENTION

[0005] According to the present invention, there is provided an injector having an orifice configured and arranged downstream of a swirler to effect a robust conical swirl pattern of the fuel ejected under pressure by the injector and at a conical spray angle angularly related to the axis of the injector such that the conical swirling spray pattern can be directed to the optimal part of the engine or fuel injection system notwithstanding the mounting of the injector at an orientation other than directed axially toward such optimal location. To accomplish this, the present invention provides an injector having an injector body with an end plate having an upstream frustoconical surface communicating upstream with a swirler to effect a swirl pattern in the fuel and an orifice downstream of the surface and which orifice has at least a flow passage portion angularly related to the axis of the injector.

[0006] In one principal form of the present invention, the orifice through the end plate can be angled relative to the axis of the injector to form an included obtuse angle. Thus, the swirl imparted to the fuel by the swirler flows smoothly about the frustoconical surface of the valve seat and effects a smooth transition to the orifice without flowing around sharp corners or into an enlarged volume or pocket. Consequently, the swirling pattern is maintained upon transitioning from the frustoconical surface into the angled opening and outwardly thereof to form the swirling conical spray pattern. It is believed that the smooth transitioning of the swirling fuel from the swirler to the outlet of the orifice without substantial flow turbulence, e.g., caused by sharp angles or turns, maintains the effectiveness of the swirler as the fuel is ejected from the injector in the conical swirl spray pattern.

[0007] In another form of the present invention, the orifice includes an opening downstream of the frustoconical surface and which opening lies on axis with the longitudinal axis of the injector. A tube is carried by the end plate and lies in communication with the opening. The tube can be directly angularly offset from the axis of the opening or, alternatively, the tube may have a first upstream portion coincident with the axis of the opening and a second downstream portion angled relative to the axis of the opening. Thus, the fuel passing through the opening in a swirling pattern continues that pattern as it passes through the tube and changes its angle relative to the longitudinal axis of the injector thereby producing

an off-axis swirling conical spray pattern.

[0008] In a preferred embodiment according to the present invention, there is provided an injector for injecting fuel into an internal combustion engine, comprising an injector body having an orifice and a longitudinal axis, a valve carried by the body and movable between open and closed positions for periodically flowing fuel through the orifice into the engine, a swirler upstream of the orifice for swirling the fuel flowing through the orifice when the valve lies in an open position, at least a portion of the orifice being configured to flow the fuel downstream thereof in a conical swirl pattern having a flow axis angularly related to the longitudinal axis.

[0009] In a further preferred embodiment according to the present invention, there is provided an injector for injecting fuel into an internal combustion engine, comprising an injector body having an orifice and a longitudinal axis, a valve carried by the body and movable between open and closed positions for periodically flowing fuel through the orifice into the engine, a swirler upstream of the orifice for swirling the fuel flowing through the orifice when the valve lies in an open position, at least a portion of the orifice having an axis forming an included obtuse angle less than 180° with the longitudinal axis and an outlet for flowing fuel from the injector in a conical swirl pattern having an axis angularly related to the axis of the orifice portion.

[0010] Accordingly, it is a primary object of the present invention to provide a novel and improved fuel injector for directing a conical swirling spray pattern of fuel to an optimum location within the engine or fuel injection system and off-axis of the injector.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011]

FIGURE 1 is a longitudinal cross-sectional view of a conventional injector;

FIGURE 2 is an enlarged cross-sectional view of the tip of an injector containing the swirler and orifice for forming a conical swirling spray pattern having an axis angularly related to the axis of the injector according to the present invention and taken about on line 2-2 of Figure 3;

FIGURE 3 is a cross-sectional view thereof taken generally about on line 3-3 in Figure 2; and

FIGURES 4, 5 and 6 disclose various forms an injector constructed in accordance with the present invention having a bent tube for effecting the angled swirling conical spray pattern.

BEST MODE FOR CARRYING OUT THE INVENTION

[0012] Referring now to the drawings, particularly to

Figure 1, there is illustrated a fuel injector for flowing fuel into an internal combustion engine. The fuel injector, generally designated 10, includes an injector body 12, a central axial passageway 14 for receiving fuel under pressure from an inlet 16 at one end of the injector and a valve assembly at its opposite end including an end plate 18 and a valve pin or needle 20. Pin 20 is periodically displaced between open and closed positions with respect to the valve seat and an orifice 19 forming part of the end plate 18. The body 12 includes windings 22, an electrical connection 24 for the windings and an armature 26 coupled to the pin or needle 20 whereby, upon receiving pulsed electrical signals, the armature causes the pin or needle to periodically open and close the valve enabling fuel to periodically flow through orifice 19. The foregoing is conventional injector construction.

[0013] A preferred form of the present invention is illustrated in Figures 2-6 and includes at the lower end of the valve body 12 an end plate 30 secured to the body 12. End plate 30 includes an orifice 32 and a frustoconical surface 34 upstream of orifice 32 forming a seat for the lower end of the valve pin or needle 20. The lower end of the body 12 includes a cavity 36 in which is disposed a disk 38 having an axially turned flange 40. Disk 38 has a plurality of holes 42 extending between its opposite sides and arranged about a central axis of the disk 38. Disk 38 also includes a central opening 44 through which passes the tip of the pin or needle 20.

[0014] Between the disk 38 and the end plate 30, there is provided a swirler disk 48. The swirler disk includes a plurality of openings 50 which, in assembly at the tip of the injector, lie in registry with the openings 42 through disk 38. Additionally, the swirler plate 48 includes passages 52 extending from each of the openings 50 in a tangential direction relative to pin 20 and defining discrete passageways for communicating fuel between the openings 50 and an annular chamber 56 about the pin or needle 20 when the latter is seated against seat 34. It will be appreciated that fuel flows under pressure about the pin 20 in an annular passage 60 toward the chamber 36. The fuel also flows through the registering openings 42 and 50 of the disk 38 and swirler plate 48, respectively, and into the passages 52 and the annular chamber 56 about pin or needle 20. When the pin or needle is in the closed position, as illustrated in Figure 2, the fuel cannot pass from the injector through the orifice 32.

[0015] Upon opening the valve, i.e., spacing the pin or needle 20 from the seat 34, fuel passes under pressure through the passageways 52 which impart a swirling motion to the fuel flow through the tip of the injector. The swirling fuel then passes between the needle or pin 20 and about the frustoconical valve seat 34 into the orifice 32. Typically, orifice 32 lies coincident with the longitudinal axis 64 of the injector. In accordance with the present invention, however, the orifice 32 has a flow passage therethrough having a central axis forming an

included obtuse angle of less than 180° with the axis 64 of the injector. Thus, the axis 66 of the orifice 32 also forms the axis of a swirling conical spray pattern, generally designated 68, emerging from the orifice 32. The conical spray pattern is characterized by a conical sheet of swirling fuel about the axis 66 with substantially only a minor quantity of fuel within the conical sheet of the conical spray pattern. The swirling effect is not significantly diminished by the structure set forth in Figures 2 and 3 because there are smooth transition areas between the swirler plate which generates the swirling flow pattern and the angled orifice 32. Thus, as illustrated in Figure 2, there is a very shallow angle at the lip of the frustoconical surface 34 which serves to smoothly transition the generally radially swirling fuel into a generally shallow conical swirl pattern about seat 34. The swirling fuel then, under pressure, passes through the orifice 32, continuing the swirling pattern. While the angle on one side of the orifice 32 is large, i.e., the left side of orifice 32 in Figure 2, the angle on the opposite side remains very shallow. Of course, angles about orifice 32 vary between the two large and shallow angles. However, it is believed that the large angle does not deleteriously affect the swirl pattern of the fuel flow because the average angle is shallow and affords a smooth flow transition which maintains the swirl flow.

[0016] Referring now to Figure 4, a particularly effective structure for affording an angular conical swirling spray pattern is illustrated. The orifice through the end plate includes an opening 70 and a tube 72 connected to the end plate 30a. For example, the opening 70 is on-axis with the longitudinal axis 64 of the injector. The tube 72 has a through flow passage having an upstream portion 74 with an axis generally coincident with the longitudinal axis of the injector. Tube 72 also includes a downstream portion 76 having an axis in its flow passage angularly related to the axis of the upstream portion and the axis of the injector. The tube 72 is essentially bent to form the angled conical swirling spray pattern. Importantly, the interior surfaces of the tube are rounded and form smooth transitions between on-axis and angularly related flows such that the swirling action of the fuel passing through the orifice is not substantially diminished as the angle of the flow changes. The orifice 70 may be counterbored at 78 and the tube 72 welded to the end plate 30a in the counterbore. Counterboring the end plate facilitates a smooth transition at the interface between the end of the tube 72 and the walls of the orifice 70.

[0017] Referring to Figure 5, wherein like reference numerals apply to like parts as in the prior embodiments, followed by the suffix "b," the end plate 30b similarly includes an opening 70b on-axis with the axis of the injector. Also, a tube 72b is secured to the end plate 30b in a counterbore 78b. The tube 72b has upstream and downstream portions 74b and 76b lying on-axis and angularly related, respectively, to the axis of the injector. A cap 80, preferably formed of powdered metal,

may be formed on the end face of the end plate 30b about tube 72b. The end face of the cap 80 may be angled to correspond to the angle of the exit opening of the tube 72b. In this manner, the projecting tube is well protected by cap 80.

[0018] Referring now to Figure 6, wherein like reference numerals apply to like parts as in the prior embodiments, followed by the suffix "c," the end plate, not shown in Figure 6, may be formed similarly as in the prior embodiments of Figures 4 and 5. In this form, however, the cap 80c may have an on-axis opening 82 for receiving the upstream portion 74c of the tube 72c, together with an off-axis recess or counterbore 84 formed in the cap opening through its lower end. By inserting the bent tube 72c in the opening 82 and securing it to the end plate, not shown in this drawing figure, the lower downstream portion 76c of the tube extends wholly through the recess 84. The recess may be filled with weld material, for example, by silver welding, affording a protective cover for the tube 72c.

[0019] In all of these embodiments, it will be appreciated that the swirl pattern afforded by the swirl plate carries through the frustoconical seat when the valve is open, as well as through the orifice in all of its various forms including the bent tubes. This is a result of smooth transitions made between a tangentially flowing fuel which ultimately continues its swirl pattern, advances axially and then is turned in an angular direction. The lack of sharp corners and protuberances avoids flow turbulence and the smooth transition surfaces afford a continuation of the strong swirl effected by the swirl plate as the fuel passes through the open valve.

[0020] While the invention has been described in connection with what is presently considered to be the most practical and preferred embodiment, it is to be understood that the invention is not to be limited to the disclosed embodiment, but on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

Claims

1. An injector for injecting fuel into an internal combustion engine, comprising:

an injector body having an orifice and a longitudinal axis; a valve carried by said body and movable between open and closed positions for periodically flowing fuel through said orifice into the engine;

a swirler upstream of said orifice for swirling the fuel flowing through said orifice when said valve lies in an open position;

at least a portion of said orifice being config-

ured to flow the fuel downstream thereof in a conical swirl pattern having a flow axis angularly related to said longitudinal axis.

2. An injector according to Claim 1 wherein said longitudinal axis coincides with a centerline of the injector and the angularly related flow axis forms an included obtuse angle with the centerline longitudinal axis.
3. An injector according to Claim 1 wherein said orifice is defined in part by a shallow, frustoconical surface downstream of said swirler affording a generally smooth transition for the swirling fuel flow from the swirler and through downstream portions of the orifice.
4. An injector according to Claim 3 wherein said injector includes an end plate having an opening forming part of said orifice, said opening having an axis angularly related to the longitudinal axis of the injector whereby the conical spray pattern has an axis generally coincident with the axis of said opening.
5. An injector according to Claim 1 wherein said injector includes an end plate having an opening therethrough forming part of said orifice, said opening having an axis generally coincident with the longitudinal axis of said injector, a tube connected to said end plate and having a flow passage in communication with said opening, said flow passage having an axis angularly related to the longitudinal axis of said injector whereby the fuel flows outwardly of the tube in a conical swirl spray pattern having an axis generally coincident with the axis of the flow passage through said tube.
6. An injector according to Claim 5 wherein the opening through said end plate has a counterbore about an exterior face of said end plate, one end of said tube being received in said counterbore, and means for coupling said tube and said end plate to one another.
7. An injector according to Claim 5 wherein said tube has a first portion having a flow axis generally coincident with the axis of said opening and a second portion having said angular flow axis further angularly related to the flow axis of said first portion.
8. An injector according to Claim 1 wherein said injector includes an end plate having an opening therethrough, a tube connected to said end plate and having an upstream portion thereof secured to said end plate and in said opening, said upstream portion having a flow passage therethrough with an axis generally coincident with the longitudinal axis

of said injector, said tube having a portion downstream of said upstream portion and having a flow passage with an axis angularly related to said upstream flow passage axis for flowing fuel outwardly of said tube in a conical spray pattern having an axis generally coincident with the axis said downstream portion.

9. An injector according to Claim 8 wherein said end plate has a recess downstream of said opening and within which recess said downstream tubular portion passes, material disposed in said recess about said downstream tubular portion for securing the tube and end plate to one another.
10. An injector for injecting fuel into an internal combustion engine, comprising:
 - an injector body having an orifice and a longitudinal axis;
 - a valve carried by said body and movable between open and closed positions for periodically flowing fuel through said orifice into the engine;
 - a swirler upstream of said orifice for swirling the fuel flowing through said orifice when said valve lies in an open position, at least a portion of said orifice having an axis forming an included obtuse angle less than 180° with said longitudinal axis and an outlet for flowing fuel from said injector in a conical swirl pattern having an axis angularly related to the axis of said orifice portion.
11. An injector according to Claim 10 wherein said orifice is defined in part by a shallow, frustoconical surface downstream of said swirler affording a generally smooth transition for the swirling fuel flow from the swirler and through downstream portions of the orifice.
12. An injector according to Claim 10 wherein said injector includes an end plate having an opening forming part of said orifice, said opening having an axis angularly related to the longitudinal axis of the injector whereby the conical spray pattern has an axis generally coincident with the axis of said opening.
13. An injector according to Claim 10 wherein said injector includes an end plate having an opening therethrough forming part of said orifice, said opening having an axis generally coincident with the longitudinal axis of said injector, a tube connected to said end plate and having a flow passage in communication with said opening, said flow passage

having an axis angularly related to the longitudinal axis of said injector whereby the fuel flows outwardly of the tube in a conical swirl spray pattern having an axis generally coincident with the axis of the flow passage through said tube.

5

14. An injector according to Claim 13 wherein the opening through said end plate has a counterbore about an exterior face of said end plate, one end of said tube being received in said counterbore, and means for coupling said tube and said end plate to one another. 10
15. An injector according to Claim 13 wherein said tube has a first portion having a flow axis generally coincident with the axis of said opening and a second portion having said angular flow axis further angularly related to the flow axis of said first portion. 15
16. An injector according to Claim 10 wherein said injector includes an end plate having an opening therethrough, a tube connected to said end plate and having an upstream portion thereof secured to said end plate and in said opening, said upstream portion having a flow passage therethrough with an axis generally coincident with the longitudinal axis of said injector, said tube having a portion downstream of said upstream portion and having a flow passage with an axis angularly related to said upstream flow passage axis for flowing fuel outwardly of said tube in a conical spray pattern having an axis generally coincident with the axis said downstream portion. 20 25 30


35

40

45

50

55






FIG. 3




FIG. 2




FIG. 4




FIG. 5




FIG. 6



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 11 6458

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	DE 195 18 950 A (NISSAN MOTOR) 30 November 1995 * column 8, line 16 - line 57 * * column 3, line 39 - column 4, line 11 * * figures 18,19 *	1-3,10, 11	F23D11/38 F23D11/26 F02M61/16 F02M61/18
X	PATENT ABSTRACTS OF JAPAN vol. 095, no. 008, 29 September 1995 & JP 07 119584 A (TOYOTA MOTOR CORP), 9 May 1995 * abstract *	1-3,10, 11	
X	GB 2 170 269 A (DAIMLER BENZ AG) 30 July 1986 * abstract * * page 2, line 128 - page 3, line 5 * * figures 1,4 *	1,2,10	
A	DE 40 32 425 A (WEBER SRL) 18 April 1991 * column 1, line 61 - column 2, line 35; figure 2 *	5,13	
A	DE 41 12 574 A (HITACHI LTD) 24 October 1991		
A	US 4 979 479 A (FURUKAWA HIROSHI) 25 December 1990		
A	DE 827 139 C (JOSEPH LUCAS)		
A,P	WO 98 35159 A (SIEMENS AUTOMOTIVE CORP LP) 13 August 1998		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 25 January 1999	Examiner Phoa, Y
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03/82 (P/M/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 11 6458

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

25-01-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 19518950 A	30-11-1995	JP 8042427 A	13-02-1996
		US 5533482 A	09-07-1996
GB 2170269 A	30-07-1986	DE 3502642 A	31-07-1986
		FR 2576642 A	01-08-1986
		JP 61175264 A	06-08-1986
		SE 459027 B	29-05-1989
		SE 8505529 A	27-07-1986
DE 4032425 A	18-04-1991	IT 221658 Z	25-07-1994
		FR 2653181 A	19-04-1991
		GB 2237065 A	24-04-1991
DE 4112574 A	24-10-1991	JP 4001438 A	06-01-1992
		JP 2589850 B	12-03-1997
		JP 4012167 A	16-01-1992
		JP 2781455 B	30-07-1998
		JP 4124437 A	24-04-1992
		DE 4143415 C	25-06-1998
		US 5140965 A	25-08-1992
US 4979479 A	25-12-1990	JP 2005753 A	10-01-1990
DE 827139 C		NONE	
WO 9835159 A	13-08-1998	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)